

GRAM FLEX-MOUNTINGS

Gram FLEX-mountings is applicable for easy mounting of e.g. fans, units, hose reels, exhaust channel exhaust channel systems or the like on walls, underneath ceilings or on roofs.

Gram FLEX-mounting is standard made in alu-zinc that provides high corrosion-resistance.



Roof bearer type FTS








Bracket type FHK

Roof bearer type FTS

Suitable for fan mounting on even roofs.

Bracket type FHK

Suitable for mounting of smaller fans on vertical walls. For larger designs, use type FKK.

Picture	Product	Bearing capacity - even spread [kg]	Dimension	Order no.
	Type FHK Bracket for fans or the like.*	75	567 x 567 x (67 x 67)	03 200 000
	Type FKK 1050 Strong bracket for fans or the like. (2 FTU 1050, 1 FTV 1050 + bolt set)	200	1050 x 1050 x 79 x 52	03 201 000
	Type FKK 1450 Strong bracket for fans or the like. (2 FTU 1450, 1 FTV 1450 + bolt set)	200	1450 x 1450 x 79 x 52	03 201 100
	Type FTS Roof bearer for even roof or the like.	100	1140 x 130 x 34	03 203 000
			1490 x 130 x 34	03 204 000
	FTU-UB U-rail	-	90 x 1140	03 203 010

* Recommended for Gram fans type VT and VL as well as VH 900 and VH 1800. For other types the stronger version is recommended.